

SAFETY DATA SHEET Tuskbond FC13 Foam Cleaner Aerosol

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Tuskbond FC13 Foam Cleaner Aerosol

Container size 500ml

EU REACH registration notes All chemicals used in this product have been registered under REACH where required.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Foam Cleaner Use only for intended applications.

Emergency telephone number

National emergency telephone National Poisons Information Service (UK): 0844 892 0111 (healthcare professionals only)

number NHS: 111 (members of the public)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms





Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H319 Causes serious eye irritation.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current UK criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

10-30%

Classification

Flam. Gas 1A - H220 Press. Gas (Liq.) - H280

ALCOHOLS, C9-C11, ETHOXYLATED

1-5%

CAS number: 68439-46-3

Classification

Acute Tox. 4 - H302 Eye Dam. 1 - H318

1-METHOXY-2-PROPANOL

<1%

CAS number: 107-98-2 EC number: 203-539-1

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336

Tuskbond FC13 Foam Cleaner Aerosol

ISOPROPANOL <1%

CAS number: 67-63-0 EC number: 200-661-7

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

SODIUM NITRITE <1%

CAS number: 7632-00-0 EC number: 231-555-9

M factor (Acute) = 1

Classification

Ox. Sol. 3 - H272 Acute Tox. 3 - H301 Eye Irrit. 2 - H319 Aquatic Acute 1 - H400

The full text for all hazard statements is displayed in Section 16.

Composition comments Liquefied petroleum gases (CAS: 68476-85-7) contains less than 0.1% w/w 1,3-butadiene,

meaning that the full harmonised classification regarding Muta. 1B H340 and Carc. 1A H350

does not apply. This product does not contain nanoforms.

Ingredient notesWhere required, the acute toxicity estimate (ATE) for any substance is listed in Section 11.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. If breathing stops, provide artificial respiration.

Keep affected person warm and at rest. Get medical attention immediately.

Ingestion Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any

discomfort continues.

Skin contact Rinse immediately with plenty of water. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Remove any

contact lenses and open eyelids wide apart. Get medical attention promptly if symptoms occur

after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation At high concentrations, vapour can acts as an asphyxiant.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact There may be irritation and redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Show this safety data sheet to the doctor in attendance.

SECTION 5: Firefighting measures

Tuskbond FC13 Foam Cleaner Aerosol

5.1. Extinguishing media

Suitable extinguishing media Water spray, foam, dry powder or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

May explode when heated or when exposed to flames or sparks. The product is extremely Specific hazards

flammable.

5.3. Advice for firefighters

Protective actions during

firefighting

Use water spray to reduce vapours. Containers can burst violently or explode when heated, due to excessive pressure build-up. Cool aerosol containers exposed to heat with water spray

and remove container, if no risk is involved.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No smoking,

sparks, flames or other sources of ignition near spillage.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

> clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers

and seal securely.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. The product

contains a substance which is hazardous to aquatic organisms and which may cause long

term adverse effects in the aquatic environment. See section 12.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's

recommendations. Avoid inhalation of vapours and spray/mists. Do not spray on a naked flame or any incandescent material. When sprayed on a naked flame or any incandescent

material the aerosol vapours can be ignited.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Extremely flammable aerosol. Store in tightly-

> closed, original container in a dry, cool and well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Do not pierce or burn, even after use.

Storage class Extremely Flammable Aerosol

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 375 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 560 mg/m3(Sk)

ISOPROPANOL

Long-term exposure limit (8-hour TWA): WEL 999 mg/m³ 400 ppm Short-term exposure limit (15-minute): WEL 1250 mg/m³ 500 ppm WEL = Workplace Exposure Limit.

Ingredient comments

WEL = Workplace Exposure Limits

ISOPROPANOL (CAS: 67-63-0)

DNEL Consumer - Oral; Long term systemic effects: 26 mg/kg

Workers - Dermal; Long term systemic effects: 888 mg/kg Consumer - Dermal; Long term systemic effects: 319 mg/m³ Consumer - Inhalation; Long term systemic effects: 89 mg/m³ Workers - Inhalation; Long term systemic effects: 500 mg/m³

PNEC - Fresh water; 140.9 mg/l

Sediment (Freshwater); 552 mg/kg
Intermittent release; 140.9 mg/l
Sediment (Marinewater); 552 mg/kg

- marine water; 140.9 mg/l

STP; 2251 mg/lSoil; 28 mg/kg

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Observe any occupational exposure limits for the product or ingredients. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof electrical, ventilating and lighting equipment. Ensure operatives are trained to minimise exposure.

Eye/face protection

Wear chemical splash goggles. Personal protective equipment that provides appropriate eye and face protection should be worn.

Hand protection

Nitrile rubber. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. Frequent changes are recommended. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated.

Tuskbond FC13 Foam Cleaner Aerosol

Other skin and body

protection

Provide eyewash station. Avoid contact with skin. Wear suitable coveralls to prevent exposure

to the skin.

Hygiene measures Good personal hygiene procedures should be implemented. Promptly remove any clothing

that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and

using the toilet.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly-

ventilated spaces, a supplied-air respirator must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. When spraying, wear a respirator fitted with the following cartridge:

Gas filter, type AX.

Thermal hazards Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with

skin.

Environmental exposure

controls

Residues and empty containers should be taken care of as hazardous waste according to

local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour White foam.

Odour Mild. Citrus

pH pH (concentrated solution): 9

Melting point No information required.

Initial boiling point and range Liquefied petroleum gases: -40 to -2°C

Flash point A flash point method is not available but the major hazardous component, the liquefied

petroleum gases, has a flash point of <-60°C with flammability limits of 10.9% vol. upper and

1.4% vol. lower.

Flammability (solid, gas) No information required.

Upper/lower flammability or

explosive limits

No information available.

Vapour pressure 2 - 5 bar @ 20°C

Vapour density Not available.

Relative density No information available.

Soluble in water.

Auto-ignition temperature Liquefied petroleum gases: 365°C

Viscosity Liquid base: Kinematic viscosity ≤ 20.5 mm²/s.

Explosive properties Not considered to be explosive.

Oxidising properties Not determined.

9.2. Other information

Particle size No information required.

Volatile organic compound This product contains a maximum VOC content of 15 %.

Tuskbond FC13 Foam Cleaner Aerosol

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable under recommended transport or storage conditions.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

No known hazardous reactions if stored under normal conditions.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition

Does not decompose when used and stored as recommended.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Summary Based on available data the classification criteria are not met.

ATE oral (mg/kg) 19,665.68

Acute toxicity - dermal

Summary Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Summary Based on available data the classification criteria are not met.

Skin corrosion/irritation

Summary Based on available data the classification criteria are not met.

Serious eye damage/irritation

Summary Causes serious eye irritation.

Respiratory sensitisation

Summary Based on available data the classification criteria are not met.

Skin sensitisation

Summary Based on available data the classification criteria are not met.

Germ cell mutagenicity

Summary Based on available data the classification criteria are not met.

Carcinogenicity

Summary Based on available data the classification criteria are not met.

Reproductive toxicity

Summary Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Tuskbond FC13 Foam Cleaner Aerosol

Summary Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

SummaryBased on available data the classification criteria are not met.

Aspiration hazard

Summary Based on available data the classification criteria are not met.

11.2. Information on other

hazards

11.2.1. Endocrine disrupting

There are no adverse health effects caused by endocrine disrupting properties.

properties

11.2.2. Other information No information available.

Toxicological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

Toxicological effects Information given is based on data of the components and of similar products.

Acute toxicity - oral

Notes (oral LD₅₀) Not applicable.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not applicable.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ >20 mg/l, Inhalation, Rat

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye Not irritating.

damage/irritation

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitroThis substance has no evidence of mutagenic properties.

Carcinogenicity

Carcinogenicity Carcinogenicity in humans is not expected.

Reproductive toxicity

Reproductive toxicity -

fertility

Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Does not contain any substances known to be toxic to reproduction.

Tuskbond FC13 Foam Cleaner Aerosol

Specific target organ toxicity - single exposure

STOT - single exposure A single exposure may cause the following adverse effects: Overexposure to

organic solvents may depress the central nervous system, causing dizziness and

intoxication and, at very high concentrations, unconsciousness and death.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Inhalation May cause respiratory system irritation.

Skin contact Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in

contact with skin.

Route of exposure Inhalation Skin and/or eye contact

ALCOHOLS, C9-C11, ETHOXYLATED

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

301.0

Species Rat

ATE oral (mg/kg) 301.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,001.0

mg/kg)

Species Rabbit

ATE dermal (mg/kg) 2,001.0

2,2',2"-Nitrilotriethanol

Acute toxicity - oral

500.0 ATE oral (mg/kg)

ISOPROPANOL

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

Species

Rat

5,045.0

5,045.0 ATE oral (mg/kg)

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 12,800.0

mg/kg)

Species Rabbit

Tuskbond FC13 Foam Cleaner Aerosol

ATE dermal (mg/kg) 12,800.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ vapours mg/l)

30.0

Species Rat

ATE inhalation (vapours

30.0

mg/l)

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye

Causes serious eye irritation.

damage/irritation

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Genotoxicity - in vivoBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity -

Based on available data the classification criteria are not met.

fertility

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

p-Cymene

Acute toxicity - inhalation

ATE inhalation (vapours 3.0

mg/l)

SECTION 12: Ecological information

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

Tuskbond FC13 Foam Cleaner Aerosol

Ecotoxicity Information given is based on data of the components and of similar products.

12.1. Toxicity

Toxicity The product contains substances which are toxic to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment. Avoid the spillage or runoff entering

drains, sewers or watercourses.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

Toxicity Not regarded as dangerous for the environment. The product is not believed to

present a hazard due to its physical nature. Highly volatile.

ALCOHOLS, C9-C11, ETHOXYLATED

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, : 1-10 mg/l, Fish

Acute toxicity - aquatic

invertebrates

LL₅₀, : 1-10 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC50,: 1-10, Algae

Acute toxicity -

microorganisms

IC₅₀, : >100 mg/l,

Chronic aquatic toxicity

Chronic toxicity - fish early NOEC, : 1-10 mg/l, Fish

life stage

Chronic toxicity - aquatic

invertebrates

NOEC, : 1-10 mg/l, Daphnia magna

ISOPROPANOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 48 hours: >100 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: >100 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅o, 72 hours: >100 mg/l, Scenedesmus subspicatus

SODIUM NITRITE

Acute aquatic toxicity

 $0.1 < L(E)C50 \le 1$ LE(C)50

M factor (Acute) 1

d-LIMONENE

Acute aquatic toxicity

 $0.1 < L(E)C50 \le 1$ LE(C)50

M factor (Acute) 1

Chronic aquatic toxicity

M factor (Chronic) 1

Hexyl Cinnamic Aldehyde

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute) 1

Pinenes

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute) 1

Chronic aquatic toxicity

M factor (Chronic) 1

Allyl Heptylate

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute) 1

C12H24O

Chronic aquatic toxicity

M factor (Chronic) 1

Camphene

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute) 1

Chronic aquatic toxicity

M factor (Chronic) 1

12.2. Persistence and degradability

Persistence and degradability Biodegradable The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in The Detergents Regulations (as amended).

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

Persistence and degradability

The product is readily biodegradable.

ALCOHOLS, C9-C11, ETHOXYLATED

Persistence and degradability

The substance is readily biodegradable.

Tuskbond FC13 Foam Cleaner Aerosol

ISOPROPANOL

Persistence and degradability

The product is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

Bioaccumulative potential Bioaccumulation is unlikely.

ALCOHOLS, C9-C11, ETHOXYLATED

Bioaccumulative potential Bioaccumulation is unlikely.

ISOPROPANOL

Bioaccumulative potential Bioaccumulation is unlikely.

Partition coefficient log Pow: 0.05

12.4. Mobility in soil

Mobility The product is soluble in water.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

Mobility The product contains volatile organic compounds (VOCs) which will evaporate

easily from all surfaces.

ALCOHOLS, C9-C11, ETHOXYLATED

Mobility Soluble in water.

ISOPROPANOL

Mobile. Soluble in water.

Surface tension 22.7 mN/m

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvBThis product does not contain any substances classified as PBT or vPvB.

assessment

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

Results of PBT and vPvB This product does not contain any substances classified as PBT or vPvB. assessment

ISOPROPANOL

Results of PBT and vPvB This product does not contain any substances classified as PBT or vPvB. assessment

12.6. Other adverse effects

12.6. Endocrine disrupting

There are no adverse effects on the environment caused by endocrine disrupting properties.

properties

12.7. Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methodsContainers should be thoroughly emptied before disposal because of the risk of an explosion.

Do not puncture or incinerate, even when empty. Dispose of waste to licensed waste disposal

site in accordance with the requirements of the local Waste Disposal Authority.

Waste class Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 10 (Containing hazardous

residues), Empty Aerosol: 15 01 04 (No hazardous residues).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

AEROSOLS

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No

14.6. Special precautions for user

IMDG Code segregation

SG69, SW1, SW22

group

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

This surfactant complies with the biodegradability criteria as laid down in The Detergents

Regulations (as amended).

Guidance ECHA: Guidance on the Compilation of safety data sheets. (V3.1, November 2015)

Authorisations (SI 2020 No.

1577 Annex XIV)

No specific authorisations are known for this product.

Restrictions (SI 2020 No.

1577 Annex XVII)

No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Classification procedures according to SI 2019 No. 720

Aerosol 1 - H222, H229: Weight of evidence. Eye Irrit. 2 - H319: Calculation method.

Issued by Technical Department

Revision date 19/12/2023

Revision 3.3

Supersedes date 27/03/2023

SDS number 22216

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H229 Pressurised container: may burst if heated.

H272 May intensify fire; oxidiser.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.